

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An apparatus for depacketizing and aligning ~~packetized input data~~ having a packetized format, comprising:

a data input interface through which the input data is transferred to the input memory, said data input interface configured to perform hand shaking with a packetized data source of said input data;

an input memory for receiving, storing, and output of ~~the input data~~, and for outputting of units of a payload of a data packet of the input data;

data processing means for receiving the outputted input data from the input memory and detecting, identifying and determining payload size of the data packet and generating a payload size signal indicative of the size of the payload, and for separately receiving and effecting data processing of the payload;

a word formatter for receiving said units of said payload outputted from the input memory, gathering and aligning said units to form data words, and for outputting said data words;

a payload counter for controlling the input memory in accordance with the payload size signal and configured to cause the payload units to be outputted from the input memory to the word formatter; and

an input buffer for receiving said data words from the word formatter and storing these them, and for transferring the data words to the data processing means; to effect said separate receiving of said payload; and ~~said data processing means for effecting said data processing using the received said data words.~~

2. (Canceled)

3. (Previously Presented) The apparatus of claim 1 wherein the input memory has a fullness level detector for generating a level-filled signal when the input data received thereby is such as to fill the input memory to a predetermined level, and said data processing means is responsive to generation of said level-filled signal to execute said receiving the outputted input data from the input memory and detecting, identifying, and determining payload size of the data packet and generating said payload size signal.

4. (Previously Presented) The apparatus of claim 3, comprising an interrupt controller for receiving said level-filled signal and generating an interrupt signal pursuant to receipt thereof, said data processing means arranged for receipt of said interrupt signal and, on receipt thereof, for executing said receiving the outputted input data from the input memory and detecting, identifying and determining payload size of the data packet therein and generating said payload size signal.

5. (Currently Amended) The apparatus of claim 4 wherein the input memory has a further fullness level detector for generating and directing to said data input interface a further level-filled signal when the input thereto of fresh input data is such as to fill the input memory to a further predetermined level, said data input interface responsive to receipt of said further level-filled signal to generate a data request signal for direction to ~~said a~~ packetized data source indicating of a need to modify the data transmission rate of the input data directed to the apparatus from the packetized data source.

6. (Currently Amended) The apparatus of claim 1 wherein the input memory is controlled whereby said input data comprising said packet is removed from the input memory and ~~replaced~~ replaced by fresh input data, pursuant to the transfer to the data processing means of said data words representing the data packet, ~~to the data~~ the apparatus being arranged for repetitive depacketizing and aligning of data packets and data processing thereof, the data processing means being arranged for repetitively and alternately executing a step comprising said receiving the outputted input data from the input memory and detecting, identifying and

determining payload size of the data packet therein and generating said payload size signal, and comprising separating receiving and effecting data processing of the payload of the data packet.

7. (Previously Presented) The apparatus of claim 1 wherein the data processing means includes a digital signal processor, data/program memory, DMA controller and input buffer, each in data communication via a bus.

8. (Previously Presented) The apparatus of claim 7 wherein the word formatter is arranged for generating a DMA request signal when a said data word is formed thereby, and the DMA controller is responsive to said DMA request signal to generate and direct a transfer signal to the digital signal processor, the digital signal processor being responsive to the transfer signal to enable the DMA controller to move the data word from the word formatter to the input buffer for subsequent processing.

9. (Previously Presented) The apparatus of claim 5 wherein said input memory is a first in first out memory.

10. (Previously Presented) The apparatus of claim 1 wherein the data processing means is arranged to execute said detecting and identifying the data packet by detection of a sync-word, followed by verification of the packet ID.

11. (Previously Presented) The apparatus of claim 1 wherein the data processing means, pursuant to said detecting and identifying the data packet, extracts timing information from the input data.

12. (Previously Presented) The apparatus of claim 1 wherein the data processing means, pursuant to said detecting and identifying the data packet, extracts side information from the input data.

13. (Currently Amended) A method for depacketizing and aligning ~~packetized~~ input data having a packetized format, comprising:

receiving and storing the input data in an input memory by transferring input data to the input memory via a data input interface that performs hand shaking with a packetized data source of said input data;

outputting the stored input data to data processing means;

by use of the data processing means, detecting, identifying and determining ~~the~~ a size of a payload of a data packet of the input data that is outputted thereto;

by use of the data processing means, generating a payload size signal indicative of the size of the payload;

controlling the input memory in accordance with the payload size signal to cause payload units that form said payload to be outputted from the input memory to ~~the~~ a word formatter;

by use of said word formatter, gathering and aligning said payload units outputted thereto to form data words;

outputting said data words from said word formatter to an input buffer and storing ~~these~~ them in said input buffer;

transferring said data words to the data processing means; and

effecting data processing on the data packet represented by the data words transferred thereto using the transferred data words.

14. (Canceled)

15. (Previously Presented) The method of claim 13 comprising generating a level-filled signal when the input data received by the input memory is such as to fill the input memory to a predetermined level, and causing said data processing means to effect said detecting, identifying, and determining payload size of the data packet, and to said generate payload size signal, pursuant to generation of the level-filled signal.

16. (Currently Amended) The method of claim ~~13~~ 15, comprising generating an interrupt signal from said level-filled signal and directing said interrupt signal to said data processing means to cause said data processing means to effect said receiving the outputted input data from the input memory and detecting, identifying, and determining payload size of ~~the a~~ data packet therein and to generate said payload size signal.

17. (Currently Amended) The method of claim 15, comprising generating and directing to ~~said a~~ data input interface a further level-filled signal when the input thereto of fresh input data is such as to fill the input memory to a further predetermined level, and causing said data input interface to generate, responsive to receipt thereby of said further level-filled signal, a data request signal for direction to ~~said a~~ packetized data source, indicative of a need to modify ~~the a~~ data transmission rate of the input data directed to the apparatus from the packetized data source.

18. (Currently Amended) The method of claim 13 wherein the input memory is controlled whereby said input data comprising ~~a~~ said data packet is removed from the input memory and ~~replaced~~ replaced by fresh input data pursuant to the transfer of said data words representing that data packet to the ~~data processor~~ processing means, and comprising receiving the outputted input data from the input memory and detecting, identifying, and determining payload size of the data packet therein and generating said payload size signal indicative of the size of the payload, and comprising effecting data processing of the payload are repetitively and alternately executed.

19. (Currently Amended) The method of claim 18, comprising generating a DMA request signal when a said data word is formed, and applying the DMA request signal to a digital signal processor forming part of said data processing means to cause the digital signal processor to enable a DMA controller to move that data word from the word formatter to an input buffer of the ~~data processor~~ processing means for subsequent processing.

20. (Previously Presented) The method of claim 13 wherein said input memory is a first in first out memory.

21. (Previously Presented) The method of claim 13 wherein the data processing means executes said detecting and identifying the data packet by detection of a sync-word, followed by verification of the packet ID.

22. (Previously Presented) The method of claim 13 wherein the data processing means extracts timing information from the input data pursuant to said detecting and identifying the data packet.

23. (Previously Presented) The method of claim 13 wherein the data processing means extracts side information from the input data pursuant to said detecting and identifying the data packet.

24. (Currently Amended) An apparatus for depacketizing and aligning packetized input data having a packetized format, comprising:

an input memory for receiving, storing, and output of the input data, and for outputting of units of a payload of a data packet of the input data;

a data input interface through which the input data is transferred to the input memory, said data input interface configured to perform hand shaking with a packetized data source of said input data;

data processing means for receiving the outputted input data from the input memory and detecting, identifying, and determining payload size of the data packet and generating a payload size signal indicative of the size of the payload, and for separately receiving and effecting data processing of the payload;

a word formatter for receiving said units of said payload outputted from the input memory, gathering and aligning said units to form data words, and outputting said data words;

a payload counter for controlling the input memory in accordance with the payload size signal whereby to cause the payload units to be outputted from the input memory to the word formatter; and

means for transferring the data words to the data processing means to effect said separate receiving of said payload.

25. (Currently Amended) A method for depacketizing and aligning packetized-input data having a packetized format comprising:

receiving and storing the input data in an input memory by transferring input data to the input memory via a data input interface that performs hand shaking with a packetized data source of said input data;

outputting the stored input data to data processing means;

by use of the data processing means, detecting, identifying, and determining the size of a payload of a data packet of the input data outputted thereto;

by use of the data processing means, generating a payload size signal indicative of the size of the payload;

controlling the input memory in accordance with the payload size signal to cause payload units that form said payload to be outputted from the input memory to the word formatter;

by use of said word formatter, gathering and aligning said payload units outputted thereto to form data words;

outputting said data words from said word formatter to an input buffer and storing ~~these~~them in said input buffer;

transferring said data words to the data processing means.

26.-29. (Canceled)